

MODEL	SPECIFICATIONS
66	(3 – 5,5V)
MOUNT TYPE	Coaxial ground-free roof mount for non-conductive surfaces with integrated active GPS antenna * BUILT-IN ACTIVE 26 dB GPS ANTENNA * LOW PROFILE DESIGN * FITS ALL STANDARD 1/2 λ ANTENNA TYPES FROM PORTABLE PROGRAMM ! (Not suitable for 1/4 λ types unless groundplane is being provided) !
GPS antenna part: ANTENNA TYPE POLARISATION FREQUENCY IMPEDANCE GAIN (LNA) NOISE FIG. POWER SUPPLY	Active ceramic patch antenna on PCB RHC (Right Hand Circular) 1575,42 MHz Nom. 50 Ω Nom. 26 dB Typ. 1.35 dB + 3,0 - 5,5 VDC (20 mA)
Combi-base part: IMPEDANCE FREQUENCY	Nom. 50 Ω 0-2500 MHz
COLOUR	Black
DIMENSIONS	80 x 53 mm
HIGHT ABOVE ROOF	Approx. 30 mm
MOUNTING-HOLE	\varnothing 18 - 22 mm (mounting from inside only)
MATERIALS	ABS, POM, PE and stainless steel
BUILD-IN DEPTH	Approx. 11 mm



CONNECTION TO ANTENNA WHIP	FME (m)
CABLE / CONNECTOR	GPS module: 0,2 m RG316/U Teflon cable and FME (m) connector Coax-Base: 0,15 m RG58C/U cable and FME (m) connector