

MODEL	SPECIFICATIONS
76	
ANTENNA TYPE	Heavy duty omni-directional DUAL BAND linear patch-antenna for trucks, vans, trailers etc. * LOW PROFILE DESIGN * CAR-WASH PROOF * NO GROUNDPLANE NEEDED
FREQUENCY IMPEDANCE POLARISATION GAIN VSWR	870-960 + 1710-1880 MHz + DECT 1850-1990 MHz + UMTS 1900-2170 MHz Nom. 50 Ω Linear 0 / 0 dB < 2.0 at frequency resonance
MAX. POWER (GSM part only)	25 Watt (low band) 10 Watt (high band)
COLOUR	Black
DIMENSIONS BUILD-IN DEPTH	Ø 92 x 16 mm Approx. 17 mm
WEIGHT	Approx. 125 g
MOUNTING	Preferable on horizontal surface (+-15° allowed) (Mounting hole Ø 12 - 20 mm)
MATERIAL	ABS, brass and PCB IP65 Classified (when mounted on vehicle)
TEMPERATURE	-40°C - +70°C
MOUNT TYPE	Bolt-on type with double self-adhesive tape for effective sealing

MODEL	CABLE / CONNECTOR (Other cable lengths and connectors available)
76/FME	0,15 m RG316/U cable and FME (m) connector
76/Fakra	0,15 m RG316/U cable and Fakra (m) connector

