

| MODEL | SPECIFICATIONS |
|------------------|---|
| 7620104 | |
| MOUNT TYPE | Roof-mounted VHF/UHF glass-fiber antenna base Rod elevation: 75° |
| FREQUENCY RANGE | VHF: 130-230 MHz 1/4 Lambda UHF: 380-510 MHz 5/8 Lambda |
| IMPEDANCE | Nom. 50 Ohm |
| COLOUR | Black |
| LENGTH (WHIP) | Approx. 570 mm (depending on freq.) |
| DIMENSIONS | 64 x 46 mm |
| HIGHT ABOVE ROOF | Approx. 44 mm |
| MOUNTING-HOLE | Ø 19 mm |
| MATERIALS | ABS, POM, PE and steel |
| BUILD-IN DEPTH | Approx. 15 mm |

| | |
|----------------------------|---|
| CONNECTION TO ANTENNA WHIP | M5 |
| CABLE / CONNECTOR | Communication: 0,15 m RG58C/U cable and FME (m) connector |

| | | |
|-------------|------|---------------|
| SPARE PARTS | WHIP | Art. No. 7620 |
|-------------|------|---------------|

| | | |
|-----------|----------------|--|
| OPTIONALS | Art. No. 15500 | Antenna Diplexer 0-225 MHz / 380-2170 MHz |
| | Art. No. 15318 | Radio Filter passive 0-108 MHz / 135-1300 MHz |
| | Art. No. 07291 | Radio Adapter cable |

