

| MODEL | SPECIFICATIONS |
|----------------|--|
| 777165 | |
| ANTENNA TYPE | Full 1/2 λ end-fed super-flexible ground-free TITANIUM antenna |
| FREQUENCY | 410-430 MHz |
| IMPEDANCE | Nom. 50 Ohm |
| POLARISATION | Vertical |
| GAIN | Approx. 5 dB compared to ¼ wave |
| BANDWIDTH | 20 MHz |
| VSWR | < 2.0 at frequency resonance |
| MAX. POWER | 25 Watt |
| COLOUR | Black |
| LENGTH | Approx. 420 mm |
| WEIGHT | Approx. 36 g |
| MOUNTING | On ground-free base |
| MATERIAL | PE, POM, TITANIUM alloy and brass |
| CONNECTOR WHIP | FME(f) |

Ground-Free Base:

| | |
|----------------------------|--|
| DIMENSIONS | Ø 33 mm x 43 mm |
| HIGHT ABOVE ROOF | Max. 30 mm (dep. on wall thickness) |
| MOUNTING-HOLE | Ø 13 mm (mounting from inside) |
| MATERIAL | ABS, POM, PE and brass |
| BUILD-IN DEPTH | 12 mm |
| CONNECTION TO ANTENNA WHIP | FME (m) |
| CABLE | RG58C/U 5m fixed cable without connector |

