

MODEL	SPECIFICATIONS
90	(3 - 5.5V)
ANTENNA TYPE	Active mobile GPS magnetic antenna * UNIVERSAL AND SIMPLE INSTALLATION * SMALL SIZE – LOW PROFILE DESIGN * WATER PROOF – NON CORROSIVE
FREQUENCY	1575,42 MHz
IMPEDANCE	Nom. 50 Ω
POLARISATION	RHC (Right Hand Circular)
GAIN (LNA) NOISE FIG.	Nom. 26 dB Typ. 1,3 dB
POWER SUPPLY	+ 3,0 – 5,5 VDC (20 mA)
VSWR	< 2.0
DIMENSIONS	\varnothing 38,5 x 12,5 mm
COLOUR	Black
BUILD-IN DEPTH	N/A
WEIGHT	Approx. 60 g (3 m cable included)
MOUNTING	Preferable on horizontal surfaces (+-15° tilt allowed)
MATERIAL	ABS, BRASS, PE and PCB
MOUNT TYPE	magnetic



CABLE/CONNECTOR	
90/F-3-FME	3 m RG174 fixed cable with FME (f) connector
90/F-3-SMA	3 m RG174 fixed cable with SMA (m) connector
90/F-5-FME	5 m RG174 fixed cable with FME (f) connector
90/F-5-SMA	5 m RG174 fixed cable with SMA (m) connector