

MODEL	SPECIFICATIONS
96	(3 - 5.5V)
ANTENNA TYPE	Mobile active GPS antenna for through-deck or bracket mounting <ul style="list-style-type: none"> • NON-CORROSIVE • LOW PROFILE DESIGN • WATER PROOF
FREQUENCY	1575,42 MHz
IMPEDANCE	Nom. 50 Ω
POLARISATION	RHC (Right Hand Circular)
GAIN (LNA) NOISE FIG.	Nom. 26 dB Typ. 1.35 dB
POWER SUPPLY	+ 3,0 - 5,5 VDC / 20 mA
VSWR	< 2.0
DIMENSIONS	Ø 47 x 15 mm
COLOUR	White
MOUNTING-HOLE BUILD-IN DEPTH	Ø 13 mm Approx. 17 mm
WEIGHT	Approx. 60 g
MOUNTING	On horizontal surface or on bracket with free sight to satellites
MATERIAL	ABS, stainless steel and brass

MOUNT TYPE	Bolt-on
CABLE / CONNECTOR	No extension cable supplied / FME (m) in base

MODEL	MOUNTING - KITS
M-917	Rail Mount (stainless steel)
M-913	Flat Surface Mount (brass and stainless steel)
M-926	Tube Mount (nylon) for M-913 / M-927
M-927	Multi Rail Mount (nylon) Ø 22, 25, 30mm



M-917



M-913



M-926



M-927